



# BARRIER

## ANTI-DEGRADATION FINISHER FOR EXTERNAL WOOD



### User guide

#### DESCRIPTION:

O/W emulsion based on vegetable waxes, paraffin, fatty acid ester, resin, and non-ionic surfactants.

#### FIELDS OF APPLICATION:

On all types of wooden surfaces placed outdoors treated with transparent varnishes, paints, dyes, impregnating agents, and oils (floors, coverings, garden furniture, structures, etc.). Ideal for reviving PVC and painted aluminum windows.

#### CHARACTERISTICS:

**BARRIER** is an anti-dirt, anti-deterioration finisher for external wooden surfaces: floors, walls, garden furniture, structures, etc.

#### **BARRIER:**

- is a water-based product, not dangerous and easy to use;
- is strongly recommended at the end of treatments with oil-wax impregnating agents (e.g. HYDROIL ESTERNO, FLUOIL, OLIO41, OLIO RAVVIVANTE), as it protects the wooden surfaces from wear and tear over time and prolongs the life of the treatment;
- forms a waxy-resin micro-layer on the material that is easy to apply, which increases resistance to wear and tear and aging and which gives further water-repellent, stain-resistant, and anti-degradation protection, with excellent resistance to UV rays;
- can also be applied to protect external surfaces (e.g. windows, doors, and windows) in aluminum, rubber, plastics, PVC, and painted wood;
- does not alter the natural aspect of the material and brightens its color;
- does not form films or glossy films and leaves a good vapor permeability to the material;
- makes surfaces easier and faster to clean.

During maintenance, it is advisable to clean the treated surface with the DETERCLEAN detergent and to apply the BARRIER product at least once every 6-12 months (in spring and autumn), in order to restore the material's protection.

#### INSTRUCTIONS FOR USE:

- Shake before using;
- Apply BARRIER in small quantities on the dry surface to be treated and distribute a thin and uniform layer with a fleece spreader, soft cloth, or sponge depending on the size of the surface to be treated;
- Do not walk on the product during drying and avoid the formation of excesses.

Generally dries in 1-2 hours.

Avoid applying to surfaces that are too heated by sunlight.

#### PRECAUTIONS:

- do not apply on painted floors;
- the use of a roller and brush is not recommended.

#### NOTES:

Our indications are based on current research knowledge and are intended to give the best indications to the buyer-user. However, these indications require preliminary examinations and tests for the fields of use, the types of materials present, and the various application conditions. The user decides independently on the suitability and field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. Rev4-Ver150322

#### WARNINGS:

**WARNINGS: NONE**

**Hazard statements:** Safety data sheet available on request.

Rev4-Ver150322

#### PACKAGING:

- 1 lt Plastic bottle – box of 6 pcs;
- 5 lt Plastic tank – box of 4 pcs.

#### YIELD:

- Approximately 1lt/ 30 – 40 m2.

#### TECHNICAL DATA:

- Physical state: white liquid
- Specific weight (g/cm3): 1
- pH: 8
- Flashpoint (ASTM): non-flammable
- Solubility in water: miscible in water
- Drying time: 30 – 60 minutes.
- Consolidation time: 24 hours

#### STORAGE:

Keep the product tightly closed at temperatures between 0°C and +30°C and not exposed to sunlight for a long time. The product stored in this way has a useful life of 2 years.

MARBEC SRL

Via Croce Rossa 51  
51037 - Montale PT  
Italia

CUSTOMER SERVICE

Tel +39 0573959848  
Whatsapp +39 3348578502  
Email [contatti@marbec.it](mailto:contatti@marbec.it)